

NEVOSIL® SY 71

Water & Oil Repellent for Construction Materials

Characteristics

Macro emulsion of silane/siloxane and synthetic resin mixture.

Properties

- ✓ Excellent surface penetration
- ✓ Fast formation of hydrophobic and oleo phobic effects
- ✓ No impairment of the water vapour permeability of the applied surfaces

Application

NEVOSIL® SY 71 in diluted form with water is used to render all types of mineral based construction and building materials water and oil repellent.

NEVOSIL® SY 71, applied by impregnation, prevents staining of facades (natural and synthetic stone, concrete, fibrous cement, and etc.) inside and outside by undesired stains/materials such as dirt, grease, graffiti, posters, etc. Oil, grease or paint can be easily removed/wiped off from the surfaces that have been treated with NEVOSIL® SY 71.

NEVOSIL® SY 71 imparts water, oil and dirt repellent properties to low-porosity natural stone, e. g. marble, travertine and granite. The product is also used to treat floors of natural or synthetic stone or unglazed ceramic tiles for easy care and for extending their lifetime.

NEVOSIL® SY 71 doesn't affect the water vapour permeability of the treated surface of building materials in any adverse way.

Technical Data

Appearance	White liquid
Active content (wt %)	30 (±1)
Viscosity (25°C)	<30 (cP)
Density (25°C)	~1,00 (g/ml)
pH	4,0–5,0

* These figures are only intended as a guide and should not be used in preparing specifications.

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants with the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials.

Editing Date: 07.03.13
Revision No/Date: -
Page: 1/2

Ultrakim Kimya San. ve Tic. A.S.
Haramidere Sanayi Sitesi M Blok
No: 322–324 Avcilar, 34840, Istanbul/Turkey
Tel: + 90 212 422 05 14
Fax: + 90 212 422 05 15
Email: info@ultrakim.com
www.ultrakim.com

NEVOSIL® SY 71

Water & Oil Repellent for Construction Materials

Processing

NEVOSIL® SY 71 should be diluted with water in ratio of 1:4 to 1:9 before using. The surface to be treated should be air dry and absorbent. The diluted solution should be liberally brushed onto surface.

The hydrophobic and oleo phobic effects should develop within 24 hours. In order to determine possible discoloration in advance, it is advisable to run trials in a small test area. This can also be used to check the efficiency of the products.

If there is any contamination of oil, grease or paint on the surface to be treated, it should be wiped out before the application. The surface should be treated with NEVOSIL® SY 71 after the surface is totally cleaned and dried.

Storage / Shelf Life

NEVOSIL® SY 71 has a shelf life up to 9 months if stored in tightly closed original containers between 5-35°C. If the material is kept beyond the shelf life recommended, it is not necessarily unusable, but quality control should be performed on the properties relevant to the application. The containers must be protected against sunlight and frost.

Packaging

30, 60, 120 and 220 kgs plastic drums or 1,000 kgs IBC containers.

The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants with the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials.

Editing Date: 07.03.13
Revision No/Date: -
Page: 2/2

Ultrakim Kimya San. ve Tic. A.S.
Haramidere Sanayi Sitesi M Blok
No: 322-324 Avcilar, 34840, Istanbul/Turkey
Tel: + 90 212 422 05 14
Fax: + 90 212 422 05 15
Email: info@ultrakim.com

www.ultrakim.com

**Technical
Data
Sheet**

NEVOSIL®